

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1 (original): A method for remotely managing a computer coupled to a communication bus, the method comprising:

- receiving, via the communication bus, a management command;
- determining whether the management command was received via a management port coupled to the communication bus; and
- when the management command was received via the management port, executing the management command.

Claim 2 (original): The method of claim 1, further comprising:

- providing, via the communication bus, data to at least one device coupled to the communication bus in response to the step of executing the management command.

Claim 3 (original): The method of claim 1, further comprising:

- when the management command was not received via the management port, ignoring the management command.

Claim 4 (original): The method of claim 1, wherein the communication bus is an IEEE 1394-compliant serial bus.

Claim 5 (original): A computer-readable medium having stored thereon computer executable instructions for performing the method of claim 1.

Claim 6 (original): A computer-readable medium having stored thereon computer executable instructions for performing the method of claim 2.

Claim 7 (original): A computer-readable medium having stored thereon computer executable instructions for performing the method of claim 3.

Claims 8-15 (canceled)

Claim 16 (original): A computer comprising:

a processor;

an IEEE 1394 interface, coupled to the processor, comprising at least one port wherein the IEEE 1394 interface passes management commands received from a management port of the at least one port to the processor and ignores any management command received via any port of the at least one port other than the management port; and

memory, coupled to the processor, having stored thereon computer executable instructions that, when executed by the processor, cause the computer to:

execute at least one management command received via the management port.

Claim 17 (original): The computer of claim 16, wherein the computer executable instructions, when executed by the processor, further cause the computer to:

provide data via any of the at least one port in response to the at least one management command received via the management port.

Claim 18 (original): The computer of claim 16, wherein the computer executable instructions, when executed by the processor, further cause the computer to:

identify one or more authorized management devices coupled to the management port.

Claim 19 (original): A system comprising the computer of claim 16, and further comprising:
an IEEE 1394-compliant serial bus coupled to the IEEE 1394 interface; and

a management device coupled, via the IEEE 1394-compliant serial bus, to the management port,

wherein the management device provides the at least one management command.

Claim 20 (original): The system of claim 19, wherein the management device is another computer.

Claim 21 (original): A computer-readable medium comprising computer-executable components for enabling remote management of a computer via a communication bus, the computer-executable components comprising:

- a bus interface component that communicates with an IEEE 1394-compliant serial bus and that receives one or more management commands via the IEEE 1394-compliant serial bus via an asynchronous or an isochronous channel; and

- a management command authorization component, in communication with the bus interface component, that determines whether each of the one or more management commands is authorized based on whether each of the one or more management commands was received via a management port coupled to the communication bus.

Claim 22 (original): The computer-readable medium of claim 21, wherein the bus interface component communicates with an IEEE 1394-compliant serial bus.

Claim 23 (original): The computer-readable medium of claim 21, further comprising:

- a host interface component, in communication with the management command authorization component and a host comprising a portion of the computer, that sends the one or more management commands to the host for execution when the one or more management commands are authorized and require host intervention.

Claim 24 (original): The computer-readable medium of claim 23, wherein the host interface component executes the one or more management commands when the one or more management commands are authorized and do not require the intervention of the host.

Claim 25 (original): The computer-readable medium of claim 23, wherein the host interface component does not send the one or more management commands to the host when the one or more management commands are not authorized.

Claim 26 (new): The computer-readable medium according to claim 21, wherein the one or more management commands are received via an asynchronous or isochronous channel.

Claim 27 (new): The computer-readable medium according to claim 26, further comprising a host interface component, in communication with the management command authorization component and a host comprising a portion of the computer, that sends the one or more management commands via the isochronous channel to the host for execution when the one or more management commands are authorized and require host intervention

Claim 28 (new): The computer-readable medium of claim 27, wherein the host interface component receives the one or more management commands via the asynchronous channel and executes the one or more management commands when the one or more management commands are authorized and do not require the intervention of the host.

Claim 29 (new): The computer-readable medium of claim 26, wherein the host interface component receives the one or more management commands via the asynchronous channel and executes the one or more management commands when the one or more management commands are authorized and do not require the intervention of the host.